



■ Viper Red

MOTOR

Tip	Rotax® 38 CP, 427 cc, 1 cilindru, racire cu lichid
Alimentare	Intelligent Throttle Control (ITC™) cu Injecție EFI
Transmisie cutie automata	Tip CVT, trepte P / R / N / H / L, cu frana de motor standard
Trenul de rulare	Selectabil 2WD / 4WD cu diferential fata auto-blocabil Visco-Lok
Categorie de viteza	Pana la 60 km/h

SUSPENSII

Suspensie fata	Brat dublu in forma de A Cursa de 9 in. (22.9 cm)
Amortizoare fata	Ulei
Suspensie spate	Brat independent Torsional Trailing (TTI) Cursa de 8.8 in. (22.4 cm)
Amortizoare spate	Ulei

ROTI / JANTE

Roti fata	Carlisle† Trail Wolf 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm)
Roti spate	Carlisle† Trail Wolf 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm)
Jante	12 in. (30.5 cm) din otel

FRANE

Fata	Doua discuri ventilate de 214 mm, cu etriere hidraulice cu doua pistoane
Spate	Disc ventilat de 214 mm, cu etriere hidraulice cu doua pistoane

DIMENSIUNI / CAPACITATI

Greutate	715 lb (324 kg)
Lungime x Latime x Inaltime	91 x 46 x 52.5 in (231 x 116.8 x 133 cm)
Ampatament	59 in. (149.9 cm)
Garda la sol	10.5 in. (26.7 cm)
Inaltime la sa	33.8 in. (85.8 cm)
Capacitate portbagaj	Fata: 120 lb (54.4 kg) / Spate: 240 lb (109 kg)
Capacitate stocare	Spate: 2.9 gal (10.9 L)
Capacitate tractare	750 kg - daca remorca este prevazuta cu sistem de franare 335 kg - daca remorca nu este prevazuta cu sistem de franare
Rezervor combustibil	5.4 gal (20.5 L)

DOTARI

Ceas digital multifunctional	Display digital 4.5 in.: Vitezometru, turometru, kilometraj, indicatori trip & ore de functionare, indicator trepte de viteze, indicator 4x4, indicator combustibil ceas
Alte dotari	Priza tip bricheta in consola, conector standard (15-A)
Sistem anti-furt	Sistem Siguranta Digital (D.E.S.S.™)
Lumini	2 faruri a cate 35 W (putere totala 70 W), stop spate
Troliu	Precablat pentru troliu
Caracteristici cat. T	Carlig de remorcare cu priza de remorca, semnalizatoare, lampi de pozitie, oglinzi, claxon
Sa	Standard