

CONSTRUCTION

HULL : Hull and structure infused in a one-shot process with balsa coring. GRP inner liner for furniture is glued with Plexus® and relaminated.

DECK : Infusion deck with foam sandwich Infusion. Light-weight inner liner in saloon moulded mast bulkhead and watertight bulkhead forward.

COCKPIT / TRANSOM

- Large, central storage locker with access via a deck hatch,
- Cockpit bench seating forward with protective coaming,
- Gas bottle storage in cockpit,
- Storage for liferaft on supports at aft end of cockpit,
- 2 winch handle holders,
- Swim ladder on stern,
- 2 tillers in composite with handles,
- Manual bilge pump near helm,
- 1 navigation compass,
- Foot hold in centre of cockpit and near helm positions.

STEERING

- Double polyester rudders and stainless steel rudder stocks,
- Self-aligning rudder bearings.

RIGGING

- Deck-stepped mast,
- 2 levels of pushing spreaders - 19/20 fractional,
- Stainless steel Dyform® shrouds,
- Adjustable backstay with returns to each helm,
- Forestay with hardware for hanked-on sail,

- Delivered without sails,
- Tricolour LED navigation lights on masthead.

RUNNING / RIGGING

- 2 multipurpose genoa halyards so that one can be used as the spinnaker pole uphaul,
- 1 doubled mainsail halyard with shackle,
- 2 masthead spinnaker halyards,
- 2 genoa sheets,
- 2 inhaulers for the genoa,
- 1 mainsheet with fine tune,
- 1 mainsail outhaul,
- Adjustment lines for mainsheet car and genoa cars,
- 2 reef lines,
- Rigid boom vang.

DECK HARDWARE

- Forward stainless steel pulpit,
- Composite bow sprit with fitting for mounting a gennaker furler,
- Aft stainless steel pushpits,
- 2 levels of lifelines with stainless steel stanchions,
- 2 mooring cleats without fairleads aft (on deck edge),
- 2 mooring cleats without fairleads forward (on deck edge),
- Anchor locker,
- Toerail moulded with the deck,
- Mainsail traveller track on cockpit floor,
- Harken deck hardware,
- Line jammers on coachroof for halyards and control lines,
- 2 winches Harken Performa for genoa and spinnaker,

- 2 winches Harken Quattro on coachroof for halyards and control lines,
- 2 turning blocks for genoa sheets,
- 2 tracks for genoa lead cars on sidedecks,
- Chainplates for shrouds on side of hull,
- Chainplates for backstay,
- Deck Step for mast with blocks,
- Handrails on coachroof.

COMPANIONWAY

- 3 steps with non-slip strips,
- Plexiglass door lockable from interior and exterior with air vents,
- Sliding GRP hatch,
- Ocean cover in GRP,
- Removable composite companionway for access to front of engine,
- Stainless steel handrails to each side of companionway.

ELECTRICAL PANEL

- Electrical panel for "offshore" use,
- 12V plug,
- Fuel gauge and voltmeter for engine battery bank
- Voltmeter for house battery bank,
- 1 engine battery 50 A/h EXIDE and 2 house batteries 120 A/h EXIDE Dryfit.

CHART TABLE

- Chart table to port with storage within desk,
- Panel for mounting electronics, designed to be compatible with a laptop and tablet computers,
- Handrail.

SALOON

- Table with folding leaves,
- 2 bench seats with back rest 2m long,
- Storage under bench seats and behind back rests,
- Fixed ports along coachroof,
- 1 opening deck hatch
- Cushions and back rests have removable covers – Sunbrella Taupe
- Removable floorboards,
- 80L water tank under saloon seating.

GALLEY

- L-galley to starboard,

- Stainless steel sink,
- Pressurised cold water tap,
- Storage for flatware and rubbish bag mount,
- 1 burner hob,
- 60 L icebox,
- Fixed port above galley,
- Handrail in facade.

AFT CABINS

- Double berth 2.00m long,
- Mattresses with removable fabric covers,
- 1 large port opening into the cockpit per cabin,
- 2 fabric hanging lockers in each cabin,
- Complete access to engine compartment,
- Access to battery switches,
- Cabin doors of the same fabric as the hanging lockers.,
- Holding tank.

HEAD COMPARTMENT

- Finished in GRP,
- Head access via sliding door in composite forward bulkhead,
- Sink with pressurised shower fixture,
- Drainage of compartment via bilge,
- 1 opening deck hatch,
- 1 marine head with manual pump.

FORWARD SECTION

- Composite watertight bulkhead with through access via deck hatch.

ENGINE

- Engine throttle in the cockpit with removable handle,
- Engine panel,
- Sound insulation for engine compartment,
- Access via removable companionway,
- Diesel engine Yanmar 3YM20C - 21 HP,

- Saildrive SD20 transmission,
- 125 A alternator,
- 2-blade folding propeller Flex-o-Fold,
- Fuel filter,
- Raw water filter,
- Anti-siphon gooseneck,
- 75L roto moulded fuel tank.

MISCELLANEOUS

- Keel mixed lead / iron with an epoxy surface treatment,
- Owner's manual,
- 3 winch handles,
- all through-hulls are flush-mounted,
- Bilge sump.


HEADROOM

- Companionway: 1,84 m
- Forward end of saloon: 1,75 m
- Aft cabins: 2,03 m

OPTIONS

- Running rigging for symmetrical spinnaker and carbon spinnaker pole,
- Removable drum genoa furler - Harken,
- Carbon-fibre mast,
- German sheeting with 2 additional winches
- Headstay foil - Harken,
- Long, composite bow sprit
- Twin wheel steering in place of twin tillers
- Shorepower, 40 A battery charger and 2 additional 120 A/h EXIDE Dryfit batteries,
- Lee cloth kit for all berths,
- B&G electronics package,
- 2 instrument repeaters mounted on mast,
- B&G Zeus² GPS at the chart table with WiFi router,
- B&G autopilot,
- Straight lead keel.

Polar plots and data can be viewed at :
www.sunfast.fr



 www.sunfast.fr